
Overview of Polarimetry at RHIC and

Elastic $p^{\uparrow}C \rightarrow pC$ Scattering at Very Low Momentum Transfer t

A. Bravar, I. Alekseev, L. Ahrens, M. Bai, G. Bunce, S. Dhawan, H. Huang, V. Hughes, G. Igo, O. Jinnouchi, K. Kurita, Z. Li, W.W. MacKay, S. Rescia, T. Roser, N. Saito, H. Spinka, D. Svirida, D. Underwood, C. Whitten, J. Wood




Polarimetry: Impact on Spin Physics




- measured spin asymmetries normalized by P_B to extract Physics Spin Observables
 - normalization \Rightarrow scale uncertainty
- polarimetric process with large σ and known A_N
 - -pC elastic scattering in CNI region
 - A_N almost calculable, but small $\sim 1-4 \%$
 - need absolute "calibration"
- RHIC Spin Program requires $\Delta P_{beam} / P_{beam} < 0.05$



Elastic $pC \rightarrow pC$ scattering at low t





- 1. A_N from interference of spin non-flip and spin flip amplitudes
 - ⇒ spin dependence of interaction
 - ⇒ hadronic spin flip (spin-coupling of Pomeron)
- 2. Polarimetry
 - almost "calculable"
 - small $A_N \sim 1-4 \% \Rightarrow$ requires large statistics $> 10^7$
 - large cross section
 - weak beam momentum dependence (p > 20 GeV/c) ?



A_N: from where does it come?

$$\sigma = |A_{\text{hadronic}} + A_{\text{Coulomb}}|^2 \quad (|P + \gamma|^2)$$

around t ~ -10^{-3} (GeV/c)² A_{hadronic} \approx A_{Coulomb} \Rightarrow INTERFERENCE CNI = Coulomb – Nuclear Interference

unpolarized \Rightarrow clearly visible in the cross section d σ /dt (charge)

polarized \Rightarrow left – right asymmetry A_N

(magnetic moment)

$$A_{N} = C \Phi_{em}^{flip} \Phi_{had}^{non-flip} + C_{2} \Phi_{had}^{non-flip} \Phi_{had}^{flip}$$

$$\propto (\mu - 1)_{p} \qquad \propto \sqrt{\sigma_{had}^{pp}}$$


QED \Rightarrow "calculable", expect $A_N \neq 0$ up to 4 - 5%

$$A_N = \sqrt{\frac{8\pi Z\alpha}{m_p^2 \sigma_{tot}^{pA}}} \frac{y^{\frac{3}{2}}}{1+y^2} (\mu - 1); \qquad y = \frac{\sigma_{tot}^{pA} t}{8\pi Z\alpha}$$


QCD ⇒ "unpredictable", need direct measurement

$$g_{5}(s,t) = \tau(s) \cdot \sqrt{|t|} / m_{p} \cdot g_{0}(s,t) \qquad g_{0}(P,f,\omega,?)$$


$$r_{5}^{pC}(s,t) = \tau(s)(i + \rho_{pC}(s,t)) = m_{p} / \sqrt{|t|} \cdot F_{s}^{had} / \Im F_{0}^{had}$$
B. Kopeliovich & L.Trueman



Some A_N measurements in CNI region




if used for polarimetry $\Rightarrow \Delta P/P \sim 15 - 20\%$






RHIC: the "Polarized" Collider

70% Polarization $L_{\text{max}} = 2 \times 10^{32} \text{ s}^{-1} \text{cm}^{-2}$ 50 < \sqrt{s} < 500 GeV



Elastic pTC Scattering Setup in the AGS Ring



similar setups in RHIC for each beam



read-out with

waveform digitizers

Event Selection


- recoil carbons detected with Si detectors
- "identified" via ToF vs T_{kin} correlation

 ⇒ inv. mass recoil
 gives only "particle ID"


position vs energy correlation spoiled by multiple scattering in target background from beam dissociation very small for this kinematics

- Δ (Tof) ~ 20 ns from bunch length ($\Rightarrow \sigma_{M} \sim 1.5 \text{ GeV}$)
- background events < few % within the "banana" cut
- very high event rate (> 10⁵ ev/sec/ch) events acquired with dead time free wave-form digitizers


 $T_{kin} = \frac{1}{2} M_R (dist / ToF)^2$ non-relativistic kinematics



Time of Flight vs. Energy i.e.




DAQ and WFD



Wave Form Digitizer = peak sensing ADC, CFD, ... deadtimless DAQ system ⇒ no spin dependent dead time! can accept, analyze, and store 1 event / each bunch ×-ing



p\c raw asymmetry at 24.3 GeV



$$P_{beam} = \frac{1}{\langle A_N \rangle} \cdot \varepsilon_N$$

$$\langle A_N \rangle = \frac{\sum N(t_i) A_N^{th}(t_i)}{\sum N(t_i)}$$

calculated over several t bins


A_Nth from a fit to E950 data at 21.7 GeV over similar t range L. Trueman hep-ph/0305085

$$\langle A_{\text{N}} \rangle \approx 1.12$$

 $0.009 < |t| < 0.022 (\text{GeV}/c)^2$



$A_N \not p \uparrow C \rightarrow p C$ at 24.3 GeV



- only statistical errors are shown
- normalization error (i.e. P_B) $\sim 25\%$ (relative)
- systematic error (background, pileup, etc.) < 20% (relative)


fit to E950 data L. Trueman hep-ph/0305085

similar behavior E950 ⇒ substantial hadronic spin-flip confirmed




AGS Polarization vs Energy (2003)

- Full spin flip at all imperfection resonances using a solenoidal partial Siberian snake
- Full spin flip at strong intrinsic resonances using an rf AC dipole (spin flipper)
- Remaining polarization losses are from coupling and weak intrinsic resonances
- Almost 2 × improvement (on avarage) compared to 2002 run
- Consistently measured polarizations of 45%; also reached 50% on occasions
- Small emittance beam of 10 π with scraping: intensity \sim 6 x 10¹⁰ p / bunch
- Add a 5% warm helical snake (run '04)
- To avoid all depolarization build a strong (20%) super-conducting helical Siberian snake snake (2005-2006)



AGS Polarization during acceleration (ramp)



Spin-03

Alessandro Bravar

Spin Dynamics

Spin Precession in Laboratory Frame: (Thomas [1927], Bargmann, Michel, Telegdi [1959])

$$dS/dt = -(e/\gamma m) [(G\gamma+1)B_{\perp} + (1+G) B_{o}] \times S$$
 $G\gamma = 1.91 E$


$$G_{\gamma} = 1.91 E$$

Lorentz Force

$$d\mathbf{v}/dt = -(e/\gamma m) \mathbf{B}_{\perp}$$

$$] \times \mathbf{v}$$

- For pure vertical field: Spin rotates Gy times faster than motion, $v_{sp} = Gy$
- For spin manipulation: at low energy, use longitudinal fields at high energy, use transverse fields





Depolarizing Spin Resonances ...

Spin tune: Number of 360 degree spin rotations (spin precessions) per turn

Depolarizing resonance condition:

Number of spin rotations per turn = Number of spin kicks per turn

<u>Imperfection resonance</u> (magnet errors and misalignments, closed orbit errors, ...):

$$G\gamma = v_{sp} = n$$

<u>Intrinsic resonance</u> (vertical focusing fields like in quadrupoles, finite beam emittance, ...):


$$G\gamma = v_{sp} = Pn \pm v_y$$

P: Superperiodicity [AGS: 12]


 $v_{\rm v}$: Betatron tune [AGS: 8.75]

Resonance conditions can be avoided through the use of "Siberian Snakes" (RHIC) or by forcing a full spin reversal, when crossing these resonances (AGS)

Imperfection Resonances: Gy = n




partial snake (AGS) = imperfection resoance




if snake sufficiently strong (5% enough in AGS) spin is fully flipped when crossing an imperfection resonance with no polarization loss

for $G\gamma \neq n$, spin "oscillates" around stable direction, which is tilted from the vertical

Intrinsic Resonances: Gy = nP + v



betatron oscillation of frequency v if spin precession "in phase" with betatron oscillation $G\gamma = v$ when crossing the quadrupole depolarizing kicks δ add \Rightarrow depolarizing resonance condition



to be in phase with betatron oscillation over a closed orbit spin must precess n + v times

in a periodic accelerator spin "in phase" with betatron oscillation when crossing same quadrupole in consecutive FODO section if


$$G\gamma = nP + v$$

Polarization losses reduced / avoided by forcing a full spin reversal (flip) using an RF dipole



$A_{N} p \uparrow C \rightarrow p C$ at 3.9, 6.5, 9.7 & 21.7 GeV

momentum transfer –t (GeV²/ c^2)



only statistical errors are shown

normalization errors:

- $\sim 10 \% \text{ (at 3.9)}$
- $\sim 15 \%$ (at 6.5)
- $\sim 20 \%$ (at 21.7)

systematic errors:

- < 20 %
- backgrounds
- pileup
- RF noise


recoil Carbon energy (keV)



Calibration of AGS pC CNI polarimeter

- Quasi-elastic *pp* scattering $p\uparrow + C \rightarrow p + p + X$ at $t \sim -0.15 \text{ GeV}^2/c^2$
- Approximately symmetric recoil telescopes of plastic scintillation counters
- Targets are thin fiber ribbons and nylon (fishline)
- For absolute calibrations forward scintillators were added


 The practical limit to this technique is P < 7 GeV/c (counters outside of beam pipe)
- Use a fit to pp polarization data to find A_N (pp) (NIM 211, 239 (1983))






Spin-03

$A_N \not p \uparrow C \rightarrow p C$: Energy Dependence



BROOKHAVEN NATIONAL LABORATORY

$A_N \not p \uparrow C \rightarrow p C$ at 21.7 GeV



normalized with

$$p\uparrow + C \rightarrow p + p + X$$

quasi-elastic polarimeter

inside AGS ring

(E880 experiment)

$$\Delta P_{beam}$$
 / P_{beam} ~ 20%


only statistical errors are shown (also for E950)

systematic error < 20%

BROOKHAVEN

recoil Carbon energy (keV)

$A_N: p \uparrow C \rightarrow p C$ at RHIC energy (100 GeV)



for normalization assume $A_N (24.3 \text{ GeV}) = A_N (100 \text{ GeV})$ i.e. no energy dependence $[0.009 < |\mathbf{t}| < 0.022 (\text{GeV}/c)^2]$


very similar shape of the *t* dependence at 24 and 100 GeV

 \Rightarrow suggestive of very small energy dependence for A_N between 24 and 100 GeV

systematic error for RHIC data < 30 %



 $A_N: p \uparrow C \rightarrow p C$ from RHIC polarimeters



assuming same A_N (E950) at 24.3 and 100 GeV




Spin-03 Alessandro Bravar

RHIC Polarization from Run '03

$$P_{beam} = \frac{1}{A_N} \cdot \varepsilon_N$$

not yet well known assume same at injection and flattop polarization on average


- at injection
 - •Blue ~ 35 40%
 - •Yellow ~ 35 40%
- at flattop
 - •Blue $\sim 25 35\%$
 - •Yellow $\sim 20 30\%$







AGS Polarization during acceleration (ramp)





Spin-03

Alessandro Bravar

BROOKHAVEN NATIONAL LABORATOR

AGS Polarization Systematics






BROOKHAVEN NATIONAL LABORATOR

A. Zelenski

Next: $p \uparrow p$, $pp \uparrow$ and $p \uparrow p \uparrow$ with a Polarized Gas Jet Target

- •RHIC absolute polarimeter calibrate pC polarimeters to < 5%
- •Polarized Hydrogen Gas Jet Target thickness of > 10¹² p/cm² polarization > 90% almost pointlike
- •Silicon recoil detectors
- •Rate: 125 Hz for $0.001 < |t| < 0.02 (\text{GeV}/c)^2$
- •Measure A_N^{pp} in pp elastic scattering in the CNI region to $\Delta A_N < 10^{-3}$ accuracy
- •Install for the '04 run
- •Initially measure P_B to 10%



Spin-03

The Polarized Jet Target under construction

Electronics racks

Vac. gauges monitors

Turbo pump controllers

Dissociator RF systems



Baffle location

Sextupoles 1-4

Sextupoles 5-6

Profile measurement

BRP vacuum vessel




_Target chamber & beam pipe adapters


Magnet ready for measurements



Jet-Target Holding Magnetic Field (1.0)



Helmholtz coils



almost no effect on recoil proton trajectories:

left – right hit profiles & left – right acceptances almost equal (also under reversal of holding field)

BROOKE


Elastic *pp* identification: $t vs \vartheta_R$


reconstructed from:

- 1. deposited energy
- 2. hit position

recoil spectrometer resolutions:

 $\Delta \theta_{\rm R} =$ targ. ext. / dist. ~ 3 mrad $|t| = 2 m_p T_{\rm kin}$; $\Delta T_{\rm kin} < 50 {\rm keV}$ $\Delta \tau \sim 2 {\rm ns}$





@FNAL $\sigma(pp \to Xp)$ at threshold $\sim 0.01 \times \sigma$ (elastic)!



The Road to P_{beam}

Requires several independent measurements

- 0 target polarization P_{target} (Breit-Rabi polarimeter)
- 1 A_N for elastic *pp* in CNI region: $A_N = 1 / P_{target} \varepsilon_N'$
- 2 $P_{beam} = 1 / A_N \epsilon_N''$ 1 & 2 can be combined in a single measurement: $P_{beam} / P_{target} = -\epsilon_N' / \epsilon_N''$ "self calibration" works for elastic scattering only
- 3 CALIBRATION: A_N^{pC} for pC CNI polarimeter in detector kinematical range: $A_N^{pC} = 1 / P_{beam} \epsilon_N'''$ (1 +) 2 + 3 measured simultaneously with several insertions of carbon target
- 4 BEAM POLARIZATION: $P_{beam} = 1 / A_N^{pC} \epsilon_N''''$ to experiments

at each step pick-up some measurement errors:

$$\frac{\Delta P_{beam}}{P_{beam}} = \left(\frac{\Delta P_{t\, arg\, et}}{P_{t\, arg\, et}}\right) \oplus \left(\frac{\Delta \varepsilon}{\varepsilon}\right)_{pp} \oplus \left(\frac{\Delta A_{N}}{A_{N}}\right)_{pC} \oplus \left(\frac{\Delta \varepsilon}{\varepsilon}\right)_{pC} \le 6\% \quad \text{expected} \quad \text{precision}$$

transfer calibration

measurement



Summary

- measured A_N^{pC} for elastic $pC \rightarrow pC$ scattering
 - $-0.005 < |t| < 0.05 (GeV/c)^2$ & $3.5 < p_{beam} < 24 GeV/c$
- $p_{beam} < 10 \text{ GeV/}c$
 - almost no *t* dependence
 - departure from "CNI" behavior
- $p_{\text{beam}} > 20 \text{ GeV/}c$
 - very similar *t* dependence at 24 and 100 GeV
 - suggestive of small (or no) energy dependence?
 - consistent with hadronic spin-flip @ 10% 15% level
- 2004 run
 - extend t range (lower and higher |t|)
 - more energy points
 - first measurements of A_N^{pp} for $pp \rightarrow pp$ with polarized gas jet target
- phenomenological analysis soon
- polarimetry
 - works reliably, fast measurements of P_{beam} in few min / 30 sec.
 - "absolute" calibration at higher energies ⇒ polarized gas jet target

